

# EtherReach™ 2118e

## **Hardware Features**

- 2x10/100BaseTX subscriber interfaces per IEEE 802.3u
- 8xE1 (ITU-T G.704) network interfaces.
- HDB3 Line coding
- Support for 128 ms differential delay on E1 interfaces
- Local craft access via: 10/100BaseTX or DB9 RS-232 serial interface

## **System Features**

### **Traffic Forwarding Modes**

- Logical circuit bonding; X.86 or GFP/VCAT/LCAS per ITU-T G.8040, G.7042, G.7043
- Configurable automatic removal / restoration of E1's from link group
- MAC Bridging with priority queuing: IEEE 802.1d
- VLAN Bridging with priority queuing per IEEE 802.1p&q
- IEEE 802.1ad (Q-in-Q) Provider Bridges
- Transparent VLAN Forwarding, tag swapping and stacking
- Programmable burst tolerance from 1ms to 20ms
- Flow Control with PAUSE frames
- 128 Policers supported per 10/100M port
- 4094 customer VLAN, 128 Service VLAN supported per 10/100M port

### **Traffic Classification and Flow Control**

- **EtherFlow™** Dynamic Flow Control for Ingress Policing with 64kb/s granularity
- 4 link layer traffic priority levels
- WRR and strict priority queue processing
- Traffic Classification and Priority via ToS/IP precedence/DSCP/802.1q&p



## **OAM and Management**

- EdgeGenie (TBD - future release) EMS/NMS
- Aligned with Carrier Ethernet OAM standards; EFM IEEE 802.3-2005 Clause 57\*, IEEE 802.1ag and ITU-T Y.1731\*
- TDR capability for LAN side cable detection
- Local and remote loop back support
- Ethernet LOS translation to DS1 AIS
- Performance Monitoring: RFC 2819 RMON, ANSI T1.231, T1.403, and GR-820
- VLAN, Port and Queue statistics for SLAs
- Inband management; remote telnet or HTTPS login
- Secure Shell Support
- SNMP v1/v2c/v3 support

## **Mechanicals**

- Width: 8 inches / 20.3 cm
- Height: 1.75 inches / 4.4cm
- Depth: 10 inches / 25.4 cm
- Optional 19" or 23" rack and tray mounts

## **Safety and Regulatory Approvals**

- MEF 9 & 14 certified
- EN 55022 Class A
- ICES 003, Issue 2
- EN 61000
- CE Mark
- UL 60950 / EN 60950
- RoHS 5/6
- Call for country specific type approvals

## **Environmental**

- Operating temp: 0 to 45 degrees C
- Storage temp: -10 to 85 degrees C
- Operating humidity: 10% to 85% non-condensing

## **Power & Heat Dissipation**

- 12 VDC via 220 VAC (90-240V) Power Adapter
- Optional -48VDC Power Adapter

\* Future release

## **Contacting Technical Support**

Users can obtain technical assistance by any of the following mail, phone, fax, and e-mail options:



A BATM Company

Web Access: <http://www.telco.com>

**BATM Advanced Communications—  
Main Support Center in Israel**

Tel: +972-4-993-5630

Fax: +972-4-993-7926

Email: [support@batm.co.il](mailto:support@batm.co.il)

**Telco Systems, A BATM Company—  
for the Americas**

Tel: 1-800-227-0937 (U.S.), 1-781-255-  
2120 (Outside U.S.)

Fax: 1-781-255-2122

Email: [techsupport@telco.com](mailto:techsupport@telco.com)

**Telco Systems, A BATM Company—  
for Northern Europe**

Tel: +49-241-463-5490

Fax: +49-241-463-5491

Email: [info@batm.de](mailto:info@batm.de)

**Telco Systems, A BATM Company—  
for Southern Europe (in France)**

Tel: +33-15-671-2773

Fax: +33-14-377-1780

Email: [support@batm.fr](mailto:support@batm.fr)

**Telco Systems, A BATM Company—  
for Asia Pacific (in Singapore)**

Tel: +65-6-725-9901

Fax: +65-6-725-9889

Email: [enquiryapac@telco.com](mailto:enquiryapac@telco.com)

**Telco Systems, A BATM Company—  
for Asia Pacific (in Japan)**

Tel: +81-3-5215-5709

Fax: +81-3-5215-5704

Email: [info.jp@telco.co](mailto:info.jp@telco.co)