

EtherReach™ 2210e

Hardware Features

- 2x10/100BaseTX subscriber interfaces per IEEE 802.3u
- 1xE3 (ITU-T G.704) network interface: 75 Ohm mini-BNC
- Local craft access via: 10/100BaseTX or DB9 serial interface

System Features

Traffic Forwarding Modes

- ITU-T X.86 or G.8040 GFP
- MAC Bridging with priority queuing: IEEE 802.1d
- VLAN Bridging with priority queuing per IEEE 802.1p&q
- IEEE 802.1ad (Q-in-Q) Provider Bridges
- Transparent VLAN Forwarding, tag swapping and stacking
- Flow Control with PAUSE frames per IEEE 802.3x
- 4094 customer VLAN, 128 Service VLAN supported per 10/100M port
- 128 Policers supported per 10/100M port

Traffic Classification and Flow Control

- **EtherFlow™** Dynamic Flow Control for Ingress Policing with 64kb/s granularity
- 4 link layer traffic priority levels per IEEE 802.1d
- WRR and strict priority queue processing
- Traffic Classification and Priority via ToS/IP precedence/DSCP/802.1q&p



OAM and Management

- EdgeGenie (TBD - future release) EMS/NMS
- Aligned with EFM IEEE 802.3-2005 Clause 57*, IEEE 802.1ag and ITU-T Y.1731*
- TDR for LAN copper cable diagnostics
- Performance Monitoring: RFC 2819 RMON
- VLAN, Port and Queue statistics for SLAs
- E3 alarms
- Inband management for remote telnet or HTTPS login
- Secure Shell Support
- SNMP v1/v2c/v3 support

Mechanicals

- Width: 8 inches / 20.3 cm
- Height: 1.75 inches / 4.45cm
- Depth: 10 inches / 25.4 cm
- Optional 19" or 23" rack and tray mounts

Safety and Regulatory Approvals

- MEF 9 & 14 certified
- EN 55022 Class A
- EN 61000
- CE Mark
- UL 60950 / EN 60950
- RoHS 5/6
- Call for country specific type approvals

Environmental

- Operating temp: 0 to 45 degrees C
- Storage temp: -10 to 85 degrees C
- Operating humidity: 10% to 85% non-condensing

Power & Heat Dissipation

- 12 VDC via 220 VAC (90-240V) Power Adapter
- Optional -48VDC Power Adapter

* Future release



Contacting Technical Support

Users can obtain technical assistance by any of the following mail, phone, fax, and e-mail options:

Web Access: <http://www.telco.com>

BATM Advanced Communications— Main Support Center in Israel

Tel: +972-4-993-5630

Fax: +972-4-993-7926

Email: support@batm.co.il

Telco Systems, A BATM Company— for the Americas

Tel: 1-800-227-0937 (U.S.), 1-781-255-2120 (Outside U.S.)

Fax: 1-781-255-2122

Email: techsupport@telco.com

Telco Systems, A BATM Company— for Northern Europe

Tel: +49-241-463-5490

Fax: +49-241-463-5491

Email: info@batm.de

Telco Systems, A BATM Company— for Southern Europe (in France)

Tel: +33-15-671-2773

Fax: +33-14-377-1780

Email: support@batm.fr

Telco Systems, A BATM Company— for Asia Pacific (in Singapore)

Tel: +65-6-725-9901

Fax: +65-6-725-9889

Email: enquiryapac@telco.com

Telco Systems, A BATM Company— for Asia Pacific (in Japan)

Tel: +81-3-5215-5709

Fax: +81-3-5215-5704

Email: info.jp@telco.co